



INSTALLATION INSTRUCTIONS

LXIHG46
NOVEMBER 5, 2009

**KITS COMMON TO COOLING
AND HEAT PUMP EQUIPMENT**

**HAIL GUARDS FOR
KGA/KCA/KHA 090**

I—APPLICATION

The Hail Guard (53W22) is designed to prevent damage to the condenser coil of the unit. The following parts are required:

II—SHIPPING AND PACKING LIST

Package 1 of 1 contains:

- 1 ea. - Hail Guard Top - Small (A)
- 2 ea. - Hail Guard Top - Large (B)
- 3 ea. - Hail Guard Side - Right (C)
- 3 ea. - Hail Guard Side - Left (D)
- 1 ea. - Hail Guard Diamond Cut - Small (E)
- 2 ea. - Hail Guard Diamond Cut - Large (F)
- 1 ea. - Hardware Package
 - 18 ea. - #10 - 16 x ½ Self Tapping Screws
 - 18 ea. - #10 - 16 x ½ Type A Screws
 - 1 ea. - Installation Instruction

⚠ CAUTION
**WHEN INSTALLING BE SURE NOT TO
PUNCTURE CONDENSER COIL.**

III—INSTALLATION

Step 1:

Remove bottom screw that hold the unit coil on right and left side.

Step 2:

Take D of large side coil align with hole pattern and secure with top and bottom screws removed in Step 1.

Step 3:

Measure the distance inside the flanges of the B. Using this distance screw C into place with self tapping screws provided.

Step 4:

Take D of large side coil align with hole pattern and secure with top and bottom screws removed in Step 1.

Step 5:

Measure the distance inside the flanges of the B. Using this distance screw C into place with self tapping screws provided.

Step 6:

Take C of small side coil align with hole pattern and secure with top and bottom screws removed in Step 1.

Step 7:

Measure the distance inside the flanges of the A. Using this distance screw D into place with self tapping screws provided.

Step 8:

Open the clips on the side panels (C & D). Slide the small diamond cut panel (E) between the clips and the front flange on side panels (C & D) until the bottom of the diamond cut panel (E) reaches the bottom of the side panel (C & D). Close the clips to secure the diamond cut panel (E).

Step 9:

Place the back flange of the small top panel (A) under the rooftop unit top panel and secure the hail guard top panel to the hail guard side panels (C & D) using the supplied #10 - 16 x ½ Type A screws.

